Scheda Tecnica

ACRIL STREET





- Acrylic paint road marking reflective and non
- Excellent resistance to abrasion
- Excellent adhesion and elasticity

Description	ACRIL STREET is a product formulated according to the current European standards. It is based on acrylic and methacrylic resins, selected and precious pigments and glass beads in accordance with the standard for the reflective type. It has an excellent resistance to abrasion and adhesion to the surface, strong refraction, rapid drying, and excellent covering power
Use	The product is used as a road marking paint on asphalt, bitumen, concrete, etc.
Appearance of the film	matt
Colour	White, yellow, and other colours
Component	1
Hardening	Physical by evaporation of solvents and oxidative polymerization.
Specific weight	1,600 gr/ ml

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Volume of solids	42%
VOC	620 gr/ liter
Minimum thickness	80 – 100 micron
Estimated yield	4,2 m² /L for a thickness of 80 microns dry
Flash point	Component A 27°C Thinner 5°C
Preparation of the product	Mix the product before use and add the thinner Component A 100 Polyurethane thinner 5 – 10 % depending on the thickness of the dry film to be applied.
Environmental conditions	Ambient temperature: from + 5 to 40°C Temperature of the surface: > 10°C Humidity: 0 – 85 % To prevent the formation of condensation the temperature of the surface must be at least 3°C higher than the dew point..

Drying and hardening times	10°C	20°C	30°C
For thicknesses of 100 microns			
Dry to touch	30	12’	5’
Dry in depth	1 h	30’	20’

Application	Spray, brush, or roller for small surfaces
Shelf life	2 years in a cool and dry place (max 40°C)
Packs	Comp A 20 kg 5 kg Thinner Lt.5, Lt. 25

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it