

COPRIFUMO



Unsaponifiable

Excellent adhesion on powder substrates

For surfaces polluted by smoke stains



Code

0825

Description

Paint based on acrylic resins modified in odourless solvents

Use

This product is suitable for walls and ceilings polluted by smoke and nicotine stains. It has good adhesion on slightly powder substrates

Appearance of the film

Matt

Color

White

Component

1

Hardening

Physical hardening through evaporation of solvents

Specific weight

1,500 gr/ml

Volume of solids

38 %

VOC

490 gr/ liter

Minimum thickness

7,5 m² / litre for a thickness of 50 microns

Flash point

Component A	34° C
Thinner	34° C

Temperature resistance

Max 110° C continuously 200° C discontinuously

Preparazione delle superfici

Lavare le superfici inquinate con idonei sgrassanti, asportare parti in fase di distacco. Applicare minimo due mani intervallate di 16 - 24 ore

Preparation of surfaces

Wash polluted surfaces with suitable degreasing products, remove all parts that are peeling off. Apply at least two coats alternated with 16 - 24 hours.

Environmental conditions

Ambient temperature: from + 5 to 40° C
 Temperature of the support: > 10° C
 Humidity: 0 - 85 %
 In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point

Drying and hardening time

For the thickness of 60 microns	10° C	20° C	30° C
Dry to touch	6	3	2 hours
Dry in depth	48	24	10 hours

Time of overpainting

Minimum (hours)	10° C	20° C	30° C
	24	12	6 hours
Maximum	unlimited in the absence of contaminants		

Application

Brush, roller, spray
If you use the brush, you have to use nylon or natural bristle brushes.
If you use the roller, you have to use medium - haired rollers.
For the application, it is necessary to use the method of crossing coats.

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A kg Thinner Lt. 5 - Lt. 25 - Lt. 180

