
Scheda Tecnica

DELUX CASA NORMALE





- Water-based paint for walls
- Excellent washability
- For internal and external use

Code	0806
Description	Water-based paint based on vinyl versatatic copolymers and precious pigments resistant to color change over time. It gives the surface a fine, velvety aesthetic effect. It is easy to apply as it has good dilatation and excellent washability. The colours in the colour chart are soft, warm and relaxing. If applied on internal walls, they give brightness to the entire home
Use	The product can be used on concrete walls where a good aesthetic appearance, as well as excellent resistance to washing with detergents, is required.
Appearance of the film	matt
Colour	White and colour chart
Componenti	1
Hardening	Physical by evaporation of water and coalescence of the polymer.

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Specific weight	from 1,430 gr/ml
VOC	40 gr/ liter
Estimated yield	8 – 9 mq /L
Flash point	Component A > 114°C
Temperature resistance	Max 60°C
Washability	> 10000 touches
Preparation of surfaces	New surfaces: Prime with acrylic insulation. In case of surfaces with high alkalinity (lime or new ready-mixed plasters) use a universal neutralizing insulator, based on alkali-resistant resins. The same treatment is advisable in case of surfaces previously treated with lime or chalking
Preparation of the product	Mix the product before use and add water Component A 100 Water max 40%
Environmental conditions	Ambient temperature: from + 5 to 40°C Temperature of the surface: > 10°C Humidity: 0 – 85 % To prevent the formation of condensation the temperature of the surface must be at least 3°C higher than the dew point

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Drying and hardening time

For thicknesses of 50 microns	10°C	20°C	30°C	
Dry to touch	3	1	0,5	hrs
Dey in depth	8	4 -5	2	

Time of overpainting

Minimum (hours)	10°C	20°C	30°C
	8	4	3

Maximum Unlimited, except for the presence of contaminants on the surface

Application

Brush, roller spray
For brush applications use nylon or pure bristle brushes.
For roller applications use medium bristle rollers.
For its application use the method of the crossed hands.

Shelf life

2 years in a cool and dry place (max 40°C)

Packs

Comp A

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it