

FINISCH PAV



Unsaponifiable and resistant to the weather

It is suitable for any supports

It is resistant to the abrasion



Code

857

Description

Solvent - based paint made of modified vinyl acrylic resins, with high resistance to the atmospheric agents, alkali and with a good permeability to water vapour.

Use

This product is applied on different substrates such as: plaster, lime plaster, bituminous surfaces, fibre cement.

Appearance of the film

Semi - glossy

Color

White, red and color chart

Component

1

Hardening

Physical hardening through evaporation of solvents

Specific weight

1,3 - 1,4 gr/ml

Volume of solids

45 %

VOC	480 gr/ liter			
Minimum thickness	60 -80 micron			
Estimated yield	7,5 m² / litre for a thickness of 60 microns			
Flash point	Component A	34°C		
	Thinner	34°C		
Temperature resistance	Max 110° C continually 200° C discontinuously			
Preparation of surfaces	New metal supports: Remove dust and contaminants, such as greases and oils, from the surfaces. For new concrete Adequate dust removal: application of a diluted coat, followed after 24 hours by an other coat as it is			
Preparation of the product	Mix the product before the use and add the thinner Component A 100 Thinner max 20 % - 30 % (First coat)			
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point			
Drying and hardening time	For the thickness of 60 microns	10° C	20° C	30° C
	Dry to touch	6	3	2 hours
	Dry in depth	48	24	10 hours
Time of overpainting	Minimum (hours)	10° C	20° C	30° C
		24	12	6 hours
	Maximum	unlimited in the absence of contaminants		

Application

Brush, roller, spray
If you use the brush, you have to use nylon or natural bristle brushes.
If you use the roller, you have to use medium - haired rollers.
For the application, it is necessary to use the method of crossing coats

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A Lt. 16 Lt. 4 Thinner 5, 25, 180 lt

