Scheda Tecnica

GEL SGRASSANTE





Paint stripper

Code	1304
Description	« Sverniciatore Universale » is a product based on methylene chloride and a mixture of pure solvents that can remove paint from various substrates..
Use	It is used to easily remove thick and hard coats of nitrocellulose, synthetic and oil - synthetic paints, enamels, fillers, alcohol - based paints, polyester, polyurethane, acrylic and rust - free paints, etc. from any surface. The removal time depends on the type and the thickness of the paint.
Appearance of the film	Opalescent colour
specific weight	1.400 gr/l
Solids content	8 % + 1
VOC	1.274gr/l

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Application	By brush: Using a nylon or pure bristle brush, evenly apply a thickness of 2 - 3 mm to the surface to be stripped; wait until the paint has completely wrinkled, then remove with a spatula. Any residue can be removed with an additional application. Before starting the new painting, wash thoroughly with a thinner. Do not use paint stripper on delicate surfaces exposed to sunlight
Safety precautions	Mix well before use. Open the container carefully as it may be under pressure and after use close it carefully and store it in a cool place, away from heat sources. When applying the product, use suitable protective glasses and gloves and provide a suitable ventilation of the environment. Safety information for the user can be found in the appropriate safety data sheet.
shelf life	1 year in a cool and dry place
packs	Lt. 0,750 - 4 - 25

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it