Scheda Tecnica

IDROCOLORE





Water - based wall paint

Good washability

It is suitable for internal and external spaces

Code	0811
Description	Based on vinylversatic resins and opaque pigments, « IDROCOLORE » is a washable water - paint indicated for both internal and external applications. It has a good consistency and it is easy to apply.
Use	This product can be applied on wall surfaces, properly prepared with concrete, where a good aesthetic appearance and an excellent resistance to washing with cleansing products are required.
Appearance of the film	Matt
Color	White
Component	1
Hardening	Physical hardening through evaporation of water and union of the polymer

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Specific weight	From 1,550 gr/ml
VOC	40 gr/ liter
Estimated yield	8 - 9 m² / liter for coat
Flash point	Component A > 114°C
Temperature resistance	Max 60°C
Washability	> 6000 touches
Preparation of surfaces	New surfaces: Prime with an acrylic insulating product. In the presence of surfaces with high alcalinity (new or lime plasters based on premixed mortar), use a universal neutralizing insulating product, based on alkali resistant resins. The same treatment is recommended for surfaces previously treated with lime or powder materials.
Preparation of the product	Mix the product before the use and add water Component A 100 Water 1° coat 20 - 25 % / 2° coat 10 - 15 %
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.

Drying and hardening time				
For the thickness of 50 microns	10° C	20° C	30° C	
Dry to touch	3	1	0,5	hours
Dry in depth	8	4 - 5	2	hours

Minimum (hours)	10° C	20° C	30° C

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Time of overpainting	8 4 3 hours Maximum unlimited in the absence of contaminants
Application	Brush, roller If you use the brush, you have to use nylon or natural bristle brushes. If you use the roller, you have to use medium - haired rollers. For the application, it is necessary to use the method of crossing coats.

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Shelf life	2 years in a cool and dry place (max 40° C)
Packs	Comp A Lt. 14 Lt. 5 Lt. 2,5

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it