Scheda Tecnica

LEGNO VIVO ECO LUCIDO o SATINATO





- Water glossy finish for wood
- Odorless, not flammable
- Elastic and weather resistant

Code	0310
Description	Glossy water based trasparent paint, formulating with acrili polymer. Rapid hardening: dry film is abrasion resistant, weather and chemicals resistant.
Use	On old or new wood surfaces indoor an autdoor.
Appearance of the film	glossy and Satin
Colour	colorless
Component	1
Hardening	Water evaporation and polymer coalescence

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Specific weight	1,000 – 1,050 gr / ml
Volume of solids	33 %
VOC	40 gr/ liter
Estimated yield	9 -10 mq / litres thickness 40 microns
Flash point	ND
Preparation of surfaces	New surfaces or carried forward: Sand surfaces to remove wood fibres: resin traces is removed using a nitro thinner. Fill any imperfections, sand and vacuum the dust. Spray or brush a wood stain one coat, thinned with 10 – 20 % water. After drying (3 – 4 hours), sand the surfaces and apply a one coat of finish glossy for indoor surfaces, two coat for outdoor. Surfaces already painted: Remove old layers of paint flaking, sand surfaces. Fill any imperfections and vacuum the dust. Proceed as above
Preparation of the product	Mix well before using Water thinner: max 5%
Environmental conditions	Temperatures: from + 8 a 35°C Surface temperature: > di 5°C Umidity: 0 – 75 %
hardening	A 20°C e 65% UR 3 – 4 hours

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Application	Spray or brush
Shelf life	Two years in a cold, dry (max 40°C)
Packs	Comp A Lt. 2,5 Lt. 0,750

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it