

PITTURE PER BAGNI E CUCINE



Water-soluble anti-mould paint

Breathable paint

Suitable for indoor use



Code

0804

Description

Vinylversatic resin-based water paint, breathable, anti-mold.

Use

It can be applied to old and new plaster, concrete, gypsum and plasterboard, old paint, etc.

Appearance of the film

Matt

Color

White and colour chart

Component

1

Hardening

Physical by evaporation of water and coalescence of the polymer.

Specific weight

From 1,690 gr/ml

VOC

30 gr/ liter

Estimated yield

8 - 9 mq / l for smooth medium absorption surfaces

Flash point

Component A > 114°C

Preparation of surfaces

Make sure the substrates are well dried, if mold is present, treat the surface as follows: clean the surface with our product SD SPRAY ANTIMUFFA. Wipe dry with a damp cloth. After that, apply an even coat of SANIMUFF facade reclaiming solution and let it act for 24 to 48 hours. Then apply two coats of Bathroom and Kitchen Paint.

Remove any efflorescence and detaching paint by brushing and washing.

Prime with acrylic fixative.

Old Paints:

Remove old, detaching paints; tempera and lime-based paints should be removed by brushing and washing.

Preparation of the product

Mix the product before use and add water

Component A 100

Water max 30%

Environmental conditions

Ambient temperature: da + 5 a 40°C

Temperature of the surface: > di 10°C

Humidity: 0 - 80 %

To prevent the formation of condensation, the temperature of the surface must be at least 3 ° C higher than the dew point.

Drying and hardening time

For thicknesses of 50 microns	10°C	20°C	30°C	
Dry to the touch	3	1	0,5	ore
Dry in depth	8	4 -5	2	

Time of overpainting

Minimum: (hrs)	10°C	20°C	30°C
	8	4	3

Maximum: unlimited, except for the presence of contaminants on the surface

Application

Brush and paint roller.
For brush applications use nylon or pure bristle brushes.
For roller applications use medium-hair rollers.
For the application use the method of the crossed hands

Shelf life

2 years in a cool and dry place (max 40 ° C)

Packs

Comp A Lt. 14 Lt. 5 Lt. 2,5

