

RESIN ANTIUMIDO



Restorative paint for damp walls

Suitable for any media

Moisture barrier



Code

0831

Description

Resin Antiumido is a wall paint based on acrylic resins in solution and a hydraulic binder, which creates a barrier effect against rising dampness in interior walls, water penetration and leakage. It is a specific product for the rehabilitation of masonry contaminated with moisture, mold, and salt efflorescence, solves this problem easily and economically.

Use

For the remediation of walls, concrete structures, and wet rooms such as: kitchens, bathrooms, basements, industrial rooms, stables, garages, laundries, and as a preventive action against any infiltration or leakage of moisture

Appearance of the film

matt

Color

White

Component

1

Hardening

Physical by evaporation of solvents

Specific weight	1,500 gr/l
Volume of solids	71 +/- 1 %
VOC	425 gr/ litro
Minimum thickness	3 mq / liter
Estimated yield	34°C
Preparation of surfaces	Thoroughly clean surfaces by removing old paint, salt efflorescence, dust and other impurities. Crumbling or crumbling plasters must be restored beforehand
Preparation of the product	Mix the product before use and add the thinner Resin Antiumido 100 Mineral Ragia Thinner 5-10%
Drying and hardening time (25°C)	Out of Touch 1 h Dry to touch 2-3 h In-Depth Dry 18-24 h
Time of overpainting	Min 12 h Max unlimited in the absence of contaminants
Application	Brush, roller, spray
Shelf life	1 year in a cool and dry place (max 40° C)
Packs	Lt.2,5 - Lt. 0,750