

STELLINE IN



Water - based additive

Luminescent effect

It is suitable for internal spaces



Code

0715

Description

It is a special water - based additive for internal rooms that, mixed with our decorative paints or even washable products or water - based enamels, or transparent finishes, will give the substrate, once dried, a particular shiny effect.

Use

This product is used as a decorative product for internal places where you want to give the rooms a touch of originality.

Appearance of the film

Matt with brilliant glitter

Color

Transparent and color chart

Component

1

Hardening

Physical hardening through evaporation of water and union of the polymer

VOC

40 gr/ liter

Specific weight	1,030 gr/lt			
Estimated yield	Kg. 0,100 per each kg. of product			
Flash point	Component A > 114°C			
temperature resistance	Max 60°C			
Preparation of the product	Product ready to use. Mix well the product before the use. Component A 100			
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.			
Drying and hardening time	For the thickness of 50 microns	10° C	20° C	30° C
	Dry to touch	3	1	0,5 hours
	Dry in depth	8	4 - 5	2 hours
Time of overpainting	Minimum (hours)	10° C	20° C	30° C
		8	4	3 hours
	Maximum	unlimited in the absence of contaminants		
Application	Pour and mix well into one of our decorative products, or into washable products, water - based enamel or transparent finishes, before applying the last coat.			

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A Kg. 0,075 - Kg. 0,250

