

STELLINE UP



Transparent finish

Washable

Shiny



Code

0716

Description

Transparent finish based on acrylic resins in water emulsion for internal places, which gives the substrate already painted with any type of water - based washable paint or enamel based on water or decorative paint, a particular and very pleasant shiny effect.

Use

This product can be applied on already painted wall surfaces, concrete, plaster, suitably prepared.

Appearance of the film

Matt - shiny

Color

Transparent and color chart

Component

1

Hardening

Physical hardening through evaporation of water and union of the polymer

Specific weight

From 1,00 gr/lt

VOC	40 gr/ litre			
Flash point	Component A	> 114°C		
Temperature resistance	Max 60°C			
washability	> 15000 touches			
Preparation of surfaces	Remove any parts that are peeling off. Eliminate dust or any stains and apply the product.			
Preparation of the product	Product ready to use. Mix well the product before the use. Component A 100			
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.			
Drying and hardening times	For the thickness of 50 microns	10° C	20° C	30° C
	Dry to touch	3	1	0,5 hours
	Dry in depth	8	4 - 5	2 hours
Time for overpainting	Minimum (hours)	10° C	20° C	30° C
		8	4	3 hours
	Maximum	unlimited in the absence of contaminants		
Application	It is applied with a brush, with irregular or crossed movements, or avoiding painting the same position in the same way.			

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A Kg. 5 – Kg. 2

