

ELASTUK



Good adhesion and elasticity

Easy to sand

Suitable for indoor and outdoor use



Fondi e Stucchi

Code

0409

Description

It is an elastic filler in ready - to - use paste, reinforced with fibres and, for this reason, it is ideal for filling and leveling cement, concrete and plasterboard surfaces, both indoors and outdoors.

Use

It is suitable to eliminate imperfections, cracks, holes, micro cracks, hollows, and to level irregular surfaces. It has an excellent filling capacity of up to 10mm with minimal shrinkage. It is easy to apply and to sand and it has an excellent adhesion and hardness on the substrate. It can be applied to new and old plasters, gypsum and plasterboard surfaces, as well as on old paints provided that they are well adherent. This product can be coated with any type of water - based paint, or even with wallpaper.

Aspect of the film

White thixotropic paste

hardening

Union

Specific weight

1660 gr/l

VOC

50 gr/litre

Preparation of surfaces

The substrate must be consistent and compact; therefore, if it is not, it is necessary to consolidate the substrate in any case.
If the substrate begins to dissolve, an acrylic water or solvent - based fixative should first be used.
On new plasters, remove any efflorescence by washing and scraping, as is customary.
In the presence of old paints, remove all the parts that are peeling off.
In the case of lime or tempera - based paints, remove them by washing and scraping.

Preparation of the product

Ready to use

Environmental conditions

Ambient temperature: from + 8 to 35° C
Humidity: 0 - 75 %
Humidity of the substrate < 10 %

Drying

At 20° C and 65 % humidity Thickness 400 - 500 microns
Sandable after 4 - 5 hours depending on thickness
Overpaintable 24 hours depending on thickness

Application

spatula

shelf life

1 year in a cool and dry place (max 40° C)

Packs

Kg. 20 - kg. 5 - kg. 1