

# FRAMMENTI DI LUCE



Wall latex paint

Decorative painting



Code

0727

Description

Latex decorative paint, formulated with acrylic copolymer and with sperical extenders that give excellent opacity and with special glitter imparting the product a Glitter is when hit by light.

Use

Suitable for imparting an elegant and refined environment. Easy to apply, even by those with little pratica. Used as a decorative finish for interiors: bar, hotel, clubs, shops etc. The white base is addizionabile to the folder in order to obtain the desired color. Can be applied to any type of support, obviously pretreated.

Film appearance

Matt

Colour

White

Component

1

Hardening

Phisical evaporation and polymer's coalescence

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Specific weight            | From 1,11 gr/ml                                                                                                                                                                                                                                                                                                                                                                                                                              |
| VOC                        | 40 gr/ liter                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Dry residue                | 48%+/1                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Estimated yield            | 8-9 mq / kg for a thickness of 50 dry microns                                                                                                                                                                                                                                                                                                                                                                                                |
| Flash point                | Component A > 114°C                                                                                                                                                                                                                                                                                                                                                                                                                          |
| resistance to temperature  | Max 60°C                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Preparation of surfaces    | <p>New surfaces<br/>Sand and remove dust, apply a fixative. Apply one or two coats of suitable primer by brush or short-haired roller. After the primer has dried, apply the finish.</p> <p>Old surfaces<br/>Removing flaking parts, sanding and remove dust, level by filling, apply one coat of fixative.<br/>Apply one or two coats of suitable primer by brush or short-haired roller. After the primer has dried, apply the finish.</p> |
| Preparation of the product | Dilute to 30% with water<br>Component A 100                                                                                                                                                                                                                                                                                                                                                                                                  |
| Environmental conditions   | <p>Room temperature: from + 5 to 40°C</p> <p>Substrate temperature: &gt; di 10°C</p> <p>Humidity: 0 - 80 %</p>                                                                                                                                                                                                                                                                                                                               |

**Finish application by brush**

It is applied as a normal paint in two coats with suitable brush. Intersperse the two hands of at least 4 - 6 hours.

**Shelf life**

Two years in a cold dry place (max 40°C)

**Packs**

14 lt. 5 lt. 2,5 lt

