

LEGNO VIVO ECO LUCIDO o SATINATO



Water glossy finish for wood

Odorless, not flammable

Elastic and weather resistant



Code

0310

Description

Glossy water based transparent paint, formulating with acrilic polymer. Rapid hardening: dry film is abrasion resistant, weather and chemicals resistant.

Use

On old or new wood surfaces indoor and outdoor.

Appearance of the film

glossy and Satin

Colour

colorless

Component

1

Hardening

Water evaporation and polymer coalescence

Specific weight	1,000 - 1,050 gr / ml
Volume of solids	33 %
VOC	40 gr/ liter
Estimated yield	9 -10 mq / litres thickness 40 microns
Flash point	ND
Preparation of surfaces	New surfaces or carried forward: Sand surfaces to remove wood fibres: resin traces is removed using a nitro thinner. Fill any imperfections, sand and vacuum the dust. Spray or brush a wood stain one coat, thinned with 10 - 20 % water. After drying (3 - 4 hours), sand the surfaces and apply a one coat of finish glossy for indoor surfaces, two coat for outdoor. Surfaces already painted: Remove old layers of paint flaking, sand surfaces. Fill any imperfections and vacuum the dust. Proceed as above
Preparation of the product	Mix well before using Water thinner: max 5%
Environmental conditions	Temperatures: from + 8 a 35°C Surface temperature: > di 5°C Umidity: 0 - 75 %
hardening	A 20°C e 65% UR 3 - 4 hours

Application

Spray or brush

Shelf life

Two years in a cold, dry (max 40°C)

Packs

Comp A Lt. 2,5 Lt. 0,750

