

LUXURY



Glossy textured finish based on water

High washability

It is suitable for internal and external spaces



Prodotti Professionali

Code

0905

Description

Paint based on vinylversatic copolymers in aqueous dispersion. It is suitable for the rooms of hospitals, schools, and for all environments where a high standard of cleanliness is required.

Use

This product can be applied to old and new plasters based on hydraulic binders, concrete, plaster and plasterboard surfaces. It is also used on old organic or inorganic paints, provided they are well adherent. Avoid the application on wet or alkaline substrates.

Appearance of the film

Glossy

Color

White and color chart

Component

1

Hardening

Physical hardening through evaporation of water and union of the polymer

Specific weight	Da 1,170 gr/m				
Volume of solids	43 %				
VOC	71,53 gr/ liter				
Minimum thickness	100 micron				
Estimated yield	4,3 m ² / litre for a thickness of 100 microns				
Flash point	Component A > 114°C				
Preparation of surfaces	<p>New surfaces: Prime with an acrylic insulating product; in the presence of surfaces with high alkalinity (lime plasters), use a universal neutralizing insulating product, based on resistant alkali resins. In the presence of lime or tempera paints, remove them entirely from the surface by washing or by the abrasion. In the presence of mold, provide an adequate anti - mold treatment with suitable products.</p>				
Preparation of the product	<p>Mix the product before the use</p> <table> <tr> <td>Component A</td><td>100</td></tr> <tr> <td>Water</td><td>max 5 % to reduce the textured effect</td></tr> </table>	Component A	100	Water	max 5 % to reduce the textured effect
Component A	100				
Water	max 5 % to reduce the textured effect				
Environmental conditions	<p>Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 75 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point</p>				

Drying and hardening time

At 25° C and 65 % of humidity 1 - 2 hours

Time of overpainting

6 hours

Application

Roller, brush only for small touches.
For the roller application, use medium - grained sponge rollers.

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A Lt. 14; Lt. 5; Lt. 2,5.

