

MUROVIVO



Water-soluble anti-mould paint

Anti-condensation paint

Breathable paint



Code

0824

Description

Resin-based paint modified with hollow glass beads, to ensure a good thermal insulation and to avoid the formation of condensation.

Use

Suitable for the protection of wall surfaces in humid or condensed environments such as: bathrooms, kitchens, cellars, laundries, etc.
It can be applied on old and new plasters, on concrete, plaster and plasterboard surfaces and old paints as long as they are very tight.

Appearance of the film

Matt

Color

White and colour chart

Component

1

Hardening

Physical by evaporation of water and coalescence of the polymer.

Specific weight

Da 0,900 gr/ml

VOC

12 gr/ liter

Estimated yield

6 m²/ L for smooth medium absorption surfaces

Flash point

Component A > 114°C

Preparation of surfaces

New surfaces:
New plasters must be seasoned, cleaned and dried.
In case of mould, treat the surface with suitable healing.
Remove any efflorescence by brushing or washing.
Prime clean surfaces with acrylic fixatives.
Already painted surfaces:
Remove the detaching parts. In case of tempera or lime based paints, provide for the total removal by washing and brushing.

Preparation of the product

Mix the product before use and add water
Component A 100
Water max. 5 - 10 %

Environmental conditions

Ambient temperature: from + 8 to 40°C
Temperature of the surface: > 10°C
Humidity: 0 - 80 %
To prevent the formation of condensation, the temperature of the surface must be at least 3 ° C higher than the dew point.

Warnings:

Do not apply the product to wet or unseasoned surfaces
Do not apply the product at temperatures below 10 °C
Do not apply the product with specific humidity above 80%.

Drying and hardening times

For thicknesses of 100 microns	10°C	20°C	30°C	
Dry to the touch	3	1	0,5	hrs
Dry in depth	12	8	4	

Time for overpainting

Minimum: (hrs)	10°C	20°C	30°C
	12	8	4
Maximum: unlimited, except for the presence of contaminants on the surface			

Application

Brush and paint roller
For brush applications use nylon or pure bristle brushes.
For roller applications use medium-hair rollers.
For the application use the method of the crossed hands

Shelf life

2 years in a cool and dry place (max 40 ° C)

Packs

Comp A

