

Scheda Tecnica

PETRA





Self-polishing coating

Made of lime paste

Filling coating



Code

0724

Description

PETRA is a filling coating with a self-polishing thickness made of bicarbonate lime paste, dust marble and natural additives. It is ideal to have effects that look like the natural aspect of stone, or old plasters.

Use

It can be applied to any interior wall surface, after preparation of the support, allowing the maximum breathability, favoring the natural diffusion of humidity through the plaster and the walls and avoiding the formation of mold and bacteria over the years.

Appearance of the film

Tixotropica white paste

hardening

Coalescence of vinyl emulsion

estimated yield

1.5 - 2.2 Kg per square meter depending on the wanted effect and the method of application

Copyright 2018 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy tel. 0804912873 - email: info@resinacolor.it p.i. 00379520729 www.resinacolor.com - www.resinacolor.it



Scheda Tecnica

Preparation of surfaces

New surfaces: make sure that the supports are completely dry. If there are molds, treat the surface with suitable products. Remove possible efflorescence and paints that are peeling off with brushes and washes. Prime the surface with a coat of our product "SABBIAFOND PER MARMOREO" diluted with water to 20-25%.

Old surfaces: remove old paints that are peeling off. Tempera paintings must be removed with brushes and washes. Prime the surface with a coat of our product "SABBIAFOND PER MARMOREO" diluted with water to 20-25%.

Preparation of the product

This product is ready for use. Mix the product before use with a spatula

Environmental conditions

Ambient temperature: from + 8 to 35° C Humidity: 0 - 75 % Humidity of the support < 10 %

Drying time

20° C and 65 % UR Thickness 400 - 500 micron Sanded after 1 - 2 hours on the basis of the thickness Overpainted after 5 - 6 hours by priming with fixative

Application

After applying a coat of "SABBAFOND PER MARMOREO" in order to insure a perfect drying, proceed with the preparation of the paint with the colors of the color chart and let it stand for at least twenty-four hours.

Spread the product evenly on the surface with a steel spatula and then, depending on the desired aesthetic effect, use the appropriate tool (palette knife, trowel, brush, and so on).

Before the product is quite dry, pass again the steel spatula to press relief parts and to compact everything.

Wait about ten minutes and pass again the palette knife, which is inclined and well cleaned, on the whole surface. So you will have a shiny and smooth surface. When Petra is quite dry, you can apply, with a sponge or a glove, a coat of our product "ANTICHE CERE" as it is or diluted with water to 30%.

You can also color "ANTICHE CERE" with our toner. Or you always apply, with a sponge or a glove, a coat of our product "DELICATO" diluted with water to 30% or a coat of our product "SOFT".



Scheda Tecnica

shelf life 1 year in a cool and dry place (max 40° C)

Packs Kg. 20 Kg. 10 Kg. 2 Kg.

