Scheda Tecnica

PRIMER ALLA PLIOLITE





Unsaponifiable and resistant to the weather.

It is used as anti - dust for concrete screeds.

Code	0604
Description	Transparent product based on acrylic - styrene resins such as « Pliolite Good Year ».
Use	This product is used as a fixative insulating product for alkaline substrates before the application of emulsion or solvent - based paints. It can be used as anti - dust for concrete floors
Appearance of the film	Semi - glossy
Color	Opalescent transparent
Component	1
Hardening	Physical hardening through evaporation of solvents

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Specific weight	0,920 gr/ml
Volume of solids	20 %
VOC	600 gr/ liter
Minimum thickness	20 - 30 micron
Estimated yield	10 m² / litre for a thickness of 20 microns
Flash point	Component A 34°C Thinner 34°C
Preparation of surfaces	The substrates must be mature and clean
Preparation of the product	Component A 100 Product ready to use
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point

Drying and hardening time

For the thickness of 40 microns	10° C	20° C	30° C
Dry to touch	2	1	0,5 hours
Dry in depth	24	8	4 hours

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Time of overpainting	unlimited in the absence of contaminants
Application	Brush, roller, spray If you use the brush, you have to use nylon or natural bristle brushes. If you use the roller, you have to use medium - haired rollers. For the application, it is necessary to use the method of crossing coats
Shelf life	2 years in a cool and dry place (max 40° C)
Packs	Comp A 25 l , 5l, 1l.

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it