Scheda Tecnica

RESIN STUCCO PASTA





- Good adhesion
- It is easy to sand
- It is suitable only for internal spaces

Code	0405
Description	Modified chalk with fast drying
Use	This product is suitable for levelling on wall substrates such as cracks, hollows. It can be applied on new and old plasters, surfaces, plaster and plasterboard, old paints well adherent.
Appearance	Polvere bianca
hardening	Hydration
Specific weight	2,7 – 3 gr/ml
Preparation of surfaces	The substrate must be consistent and compact, otherwise it must be consolidated. If the substrate begins to become powder, use a water or solvent - based acrylic fixative. On new plasters, remove any efflorescence by brushing and scraping. In the presence of old paints, remove all paints that are peeling off. In the presence of lime or tempera paints, remove them by brushing and scraping.

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

resina color made in italy painting the difference

Scheda Tecnica

Preparation of the product	Mix 100 parts of powder with water in order to obtain a creamy paste
Environmental conditions	Ambient temperature: from + 8 to 35° C Humidity: 0 - 75 % Humidity of the support: < 10 %
Pot life	About 2 hours
Drying	At 20° C and 65 % UR Thickness 400 - 500 microns Sandable after 4 - 5 hours depending on the thickness Overpainted after 7 - 8 hours after the coverage with a fixative product.
Application	Whit a spatula
shelf life	1 year in a cool and dry place (max 40° C
Packs	Kg. 15 Kg. 5 Kg. 1

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it