

RESIN STUCCO PASTA



Good adhesion

It is easy to sand

It is suitable only for internal spaces



Code

0405

Description

Modified chalk with fast drying

Use

This product is suitable for levelling on wall substrates such as cracks, hollows. It can be applied on new and old plasters, surfaces, plaster and plasterboard, old paints well adherent.

Appearance

Polvere bianca

hardening

Hydration

Specific weight

2,7 - 3 gr/ml

Preparation of surfaces

The substrate must be consistent and compact, otherwise it must be consolidated. If the substrate begins to become powder, use a water or solvent - based acrylic fixative.

On new plasters, remove any efflorescence by brushing and scraping.

In the presence of old paints, remove all paints that are peeling off. In the presence of lime or tempera paints, remove them by brushing and scraping.

Preparation of the product

Mix 100 parts of powder with water in order to obtain a creamy paste

Environmental conditions

Ambient temperature: from + 8 to 35° C

Humidity: 0 - 75 %

Humidity of the support: < 10 %

Pot life

About 2 hours

Drying

At 20° C and 65 % UR Thickness 400 - 500 microns

Sandable after 4 - 5 hours depending on the thickness

Overpainted after 7 - 8 hours after the coverage with a fixative product.

Application

Whit a spatula

shelf life

1 year in a cool and dry place (max 40° C

Packs

Kg. 15 Kg. 5 Kg. 1