

RESINFILL DUO



Spatula synthetic putty

Easy application

Good adhesion and resistance



Fondi e Stucchi

Code

0407

Description

Single-component paste synthetic putty, based on alkyd and urethane resins, for wood and metal. Exceptional adhesion and surface hardness. Easy to sand both dry and wet.

Use

Suitable for application at low and medium thickness to achieve uniform surfaces. Used for the preparation of large and small surfaces, in wood and metal (properly treated).

Appearance of the film

Matt

Color

White

Components

1

Viscosity

Pasty

Elasticity

Good

Adhesion	Excellent
Hardness	Excellent
Hardening	Physical solvent evaporation
Specific weight	1.900 gr/ml
Dry residue	80%
VOC	342 gr/ litro
Estimated yield	Variable depending on thickness
Flash point	Component A > 23°C
Preparation of surfaces	Remove any traces of oil or rust, friable parts, or areas in the process of detaching through mechanical cleaning or sanding. If necessary, apply a coat of universal primer EPOFOND ZINC or CEMNTIK depending on the substrate.
Preparation of the product	Ready to use
Environmental conditions	Room temperature: from + 10 to 35°C Surface temperature: > di 10°C Humidity: 0 - 85 % To prevent the formation of condensation is necessary that the temperature of the substrate is at least 3 ° C above the dew point.

Drying and hardening time

Dry to the touch 2 hours
Through drying 24 hours

Application

Spatula

Shelf life

2 years in a cool, dry place (max 40 ° C)

Packs

Lt. 0,500

