

## Scheda Tecnica

## RESINSTUCK





Good adhesion

Easy to sand

Suitable only for internal spaces



Code

0404

Description

Filler product formulated with sintetic resins in water dispersion. It is a product easy to use, soft to apply, with fairly fast drying and excellent dry sanding.

Use

This product is suitable for leveling imperfections on wall substrates such as cracks or hollows. It can be applied on new plasters and old surfaces, plaster and plasterboard, old paints that are well adherent to the substrate

Aspect of the film

Thixotropic white paste

hardening

Coalescence of vinyl emulsion

Specific weight

1,800 gr/ml

Preparation of surfaces

The substrate must be consistent and compact, otherwise it must be consolidated. If the substrate begins to become powder, use a water or solvent - based acrylic fixative. On new plasters, remove any efflorescence by brushing and scraping. In the presence of old paints, remove all paints that are peeling off. In the presence of lime or tempera paints, remove them by brushing and scraping.

Copyright 2018 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy tel. 0804912873 - email: info@resinacolor.it p.i. 00379520729 www.resinacolor.com - www.resinacolor.it



## Scheda Tecnica

VOC 6 gr/litre Preparation of the product Mix the product well before the use with a spatula **Environmental conditions** Ambient temperature: from + 8 to 35° C 0 - 75 % Humidity: Humidity of the support: < 10 % At 20° C and 65 % UR Thickness 400 - 500 microns Drying Sandable after 1 - 2 hours depending on the thickness Overpainted after 5 - 6 hours after the coverage with a fixative product **Application** spatula 1 year in a cool and dry place (max 40° C) shelf life **Packs** Kg. 20 Kg. 25 Kg. 5 Kg. 1Kg