

SCRIVI E RISRIVI



Decorative paint

For internal places

Based on acrylic resins in water dispersion.



Code

0739

Description

It is a decorative paint that makes the surface writable with white or colored chalks. It is easily cleaned with a duster or a soft cloth. It transforms the walls in large blackboards where children can play, express their thoughts and where you can write down notes, messages, sentences, daily menu, shopping list, and so on. It makes the place where it is applied modern and playful. It is a product based on acrylic resins in water dispersion.

Use

This paint is indicated for the painting of the walls of internal places; it can be used in houses, offices, children's recreation centers, schools, relaxation areas, or in any other place where you want to create a writable wall. It is a decorative paint easy to use and it is applied as a normal paint..

Appearance of the film

Matt

Appearance

Liquid

Color

White - black - colored

Component	1
Hardening	Physical hardening through evaporation of water
Specific weight	About 1.100 gr/ml
VOC	50 gr/ liter
pH	7.0-9.0
Estimated yield	10 - 13 m ² / litre according to the absorption of the substrate
Flash point	> 100°C
Application	Fill and prime the surfaces; on the substrates very absorbent, it is necessary to give also a priming coat. Apply 3 coats of paint effect blackboard in order to obtain a good magnetic power; between the coats, it is necessary to spend at least 4 - 5 hours. The product is writable after seven days. The paint should be applied as a normal paint, using the method of crossing coats. It can be applied both with a brush and with a roller. If you choose the first option, you have to use nylon or natural bristle brushes. If you choose the second option, you have to use rollers with rubber tops or short-haired rollers.
Preparation of the product	Diluted al 10%

Environmental conditions

Ambient temperature: from + 8 to 40° C
 Temperature of the support: > 10° C
 Humidity: 0 - 80 %
 In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.

Precautions:

Do not use chalks with the point shaped like a nail (they may scratch the substrate); it is recommended to use a little the points of the chalks.
 Do not apply on wet surfaces.
 Do not apply at temperature below 10° C
 Do not apply when humidity is above 80 %

Drying and hardening time

20° C
 Dry to touch 1 hour
 Dry in depth 4 hours
 Crystallized 7 days

Time of overpainting

Minimum (hours) 20° C
 4 - 5 hours
 Maximum unlimited in the absence of contaminants

Shelf life

1 year in a cool and dry place (max 40° C)

Packs

Lt. 0,750