

SPARTITRAFFICO W



Non - refractive signs paint, solvent - free

Excellent adhesion on asphalt, cement, bitumen



Code

867

Description

Paint based on acrylic resin in emulsion with a good drying speed.

Use

This product is used as a paint for road signs to be applied on cement, asphalt, bituminous aggregates. Drying in depth is fast (30 minutes) under normal conditions (20° C - 60 % UR), but it decreases with increasing humidity and decreasing temperature.

Appearance of the film

Matt

Color

White - yellow - light blue - black

Component

1

Hardening

Physical hardening through evaporation of water and union of the polymer

Specific weight

From 1,70 - 1,75 gr/ml

Volume of solids	60 %			
VOC	45 gr/ liter			
Minimum thickness	150 micron			
Estimated yield	4 m ² / litre for a thickness of 150 microns			
Flash point	Component A > 114°C			
Preparation of surfaces	Perform an accurate cleaning by removing dust and all parts that are peeling off. The substrate must be dry; the presence of excessive humidity inside the substrate, during solar irradiation, can generate vapour that causes the formation of bubbles and the subsequent detachment of the coating.			
Preparation of the product	Mix the product before the use. Thin with 5 - 15 % max of water			
Environmental conditions	Ambient temperature: from + 10 to 40° C Temperature of the support: > 10° C Humidity: 0 - 70 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.			
Drying and hardening time	For the thickness of 150 microns	10° C	20° C	30° C
	Dry to touch	25'	12'	8'
	Dry in depth	60'	25'	15'
Application	Spray, roller If you use the roller, you have to use medium - haired rollers.			

Shelf life

1 year in a cool and dry place (max 40° C)

Packs

Comp A Lt.14

