resina color made in italy
painting the difference

Scheda Tecnica

STELLINE UP

Transparent finish

Washable

Shiny

Code	0716
Description	Transparent finish based on acrylic resins in water emulsion for internal places, which gives the substrate already painted with any type of water - based washable paint or enamel based on water or decorative paint, a particular and very pleasant shiny effect.
Use	This product can be applied on already painted wall surfaces, concrete, plaster, suitably prepared.
Appearance of the film	Matt - shiny
Color	Transparent and color chart
Component	1
Hardening	Physical hardening through evaporation of water and union of the polymer
Specific weight	From 1,00 gr/lt

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

VOC	40 gr/ litre
Flash point	Component A > 114°C
Temperature resistance	Max 60°C
washability	> 15000 touches
Preparation of surfaces	Remove any parts that are peeling off. Eliminate dust or any stains and apply the product.
Preparation of the product	Product ready to use. Mix well the product before the use. Component A 100
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.
Drying and hardening times	For the thickness of 50 microns 10° C 20° C 30° C Dry to touch 3 1 0,5 hours Dry in depth 8 4 - 5 2 hours
Time for overpainting	Minimum (hours) 10° C 20° C 30° C 8 4 3 hours Maximum unlimited in the absence of contaminants
Application	It is applied with a brush, with irregular or crossed movements, or avoiding painting the same position in the same way.

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it

Shelf life	2 years in a cool and dry place (max 40° C)
Packs	Comp A Kg. 5 – Kg. 2

Copyright 2026 Resina Color - z.i. Via Mastricale 3 - 70017 Putignano (BA) - Italy
tel. 0804912873 - email: info@resinacolor.it p.i. 09040010721
www.resinacolor.com - www.resinacolor.it