

SOFT



Transparent finish

Washable

Glossy - matt



Description

Transparent glossy or matt finish based on acrylic resins in water emulsion for the internal places and special particle - size pigments with a metallic effect, which gives a particular metallic effect to the substrate

Use

This product can be applied on already painted wall surfaces, concrete, plaster, cement, suitably prepared.

Appearance of the film

Matt - glossy

Colore

Transparent and color chart

Component

1

Hardening

Physical hardening through evaporation of water and union of the polymer

Specific weight

From 1,00 gr/lt

VOC	40 gr/ liter
Minimum thickness	40 micron
Estimated yield	4 - 5 mq/kg
Flash point	Component A > 114°C
temperature resistance	Max 60°C
washability	> 15000 touches
Preparation of surfaces	New surfaces: apply a coat of our insulating product « IMPRIMITURA ACRILICA » diluted with water in ratio 1 to 5 (mix each liter of « IMPRIMITURA ACRILICA » with 5 liters of water). Old surfaces: remove any parts that are peeling off and, after a careful cleaning of the substrate, apply a coat of our insulating product « IMPRIMITURA ACRILICA » diluted with water in ratio 1 to 5 (mix each liter of « IMPRIMITURA ACRILICA » with 5 liters of water).
Preparation of the product	Product ready to use. Mix the product well before the use. Component A 100
Environmental conditions	Ambient temperature: from + 5 to 40° C Temperature of the support: > 10° C Humidity: 0 - 85 % In order to prevent the formation of condensation, it is necessary that the temperature of the substrate is at least 3° C above the dew point.

Drying and hardening time

For the thickness of 50 microns	10° C	20° C	30° C
Dry to touch	3	1	0,5 hours
Dry in depth	8	4 - 5	2 hours

Time of overpainting

Minimum (hours)	10° C	20° C	30° C
	8	4	3 hours
Maximum	unlimited in the absence of contaminants		

Application

After an appropriate preparation of the substrate, apply the product as follows: apply a coat of white or any color primer « SABBIAFOND » with a brush or a roller diluted with water to 20 - 25 %. When the substrate is completely dry, apply a coat of « SOFT », undiluted, with the special brush, the glove or the sponge, making circular or cross movements avoiding painting the same position in the same way or in a casual way. « SOFT » can be applied on any type of water - based paints.

Shelf life

2 years in a cool and dry place (max 40° C)

Packs

Comp A Kg. 5 - Kg. 2