

MARMOREO



Self - polishing filler

Self - polishing filler

Breathable



Code

0719

Description

It is a self - polishing filler based on bicarbonate lime paste, dust marble and vegetal additives to obtain pleasant ancient effects.
Since it is a breathable product, « MARMOREO » is not a washable product. If you want to make « MARMOREO » washable, apply one or two coats of our product « ANTICHE CERE ».

Use

This product is applied to any interior wall surface, after the preparation of the substrate, allowing the greatest breathability, favoring the natural diffusion of the humidity through the plaster and the walls, and finally avoiding the formation of molds and bacteria over the years.

Appearance of the film

Thixotropic white paste

Hardening

Coalescence of vinyl emulsion

Specific weight

gr/ml

Preparation of surfaces

New surfaces: make sure that the substrates are completely dry. If there are molds, treat the surface with suitable restoring products. Remove any efflorescence and all paints that are peeling off with brushes and washes. Prime the surface with a coat of our product « SABBIAFOND PER MARMOREO » diluted with water to 20 - 25 %.

Old surfaces: remove old paints that are peeling off. Tempera paintings must be removed with brushes and washes. Prime the surface with a coat of our product « SABBIAFOND PER MARMOREO » diluted with water to 20 - 25 %.

Preparation of the product

Product ready to use. Mix the product well before the use with a spatula

Environmental conditions

Ambient temperature: from + 8 to 35° C
Humidity: 0 - 75 %
Humidity of the support: < 10 %

Drying

At 20° C and 65 % UR Thickness 400 - 500 microns
Sandable after 1 - 2 hours depending on the thickness
Overpainted after 5 - 6 hours after the coverage with a fixative product.

Application

After applying a coat of « SABBIAFOND PER MARMOREO » in order to insure a perfect anchorage, proceed with the preparation of the paint with the colors indicated on our color chart and let it stand for at least twenty - four hours.

First coat: apply « MARMOREO » on the surface with a steel spatula. Wait from 8 to 14 hours for a perfect drying and apply a second coat of « MARMOREO » with a shaving steel spatula in order to make the surface completely smooth.

Wait 8 - 10 hours for the drying. Before applying the third coat, it is recommended to mix « MARMOREO » to make it more fluid in the application.

In this way, the product will penetrate the entire surface, by closing any cracks and making the support perfectly smooth. The application of the third coat must be carried out with a steel spatula in an inclined position in the way "metto e tolgo" ("put and remove") for about 1 square metre.

Wait about 30 seconds and pass again the spatula, always in an inclined position and well clean. Proceed in this way on the entire surface overlapping with the previous coat in order to eliminate any junction marks. In this way, you will obtain a surface, that is completely glossy and soft to the touch.

Shelf life

1 year in a cool and dry place (max 40° C)

Packs

Kg. 20 Kg. 10 Kg. 2 Kg.

